

WL 2000 IT

An effective POU cooler dispensing safe, clean drinking water for the workplace without the hassle of bottles. This smart looking WL2000IT uses in-tank UV technology to chill and purify water directly from the mains supply. Our carbon filtration system means it tastes beautiful too so quality and safety are guaranteed.

Simply put, Great Water

Three Steps to Greatness

This Waterlogic dispenser has 3 core technologies which mean that what you get out of your machine is much better than what goes in:



1. Filtration: our filtration technology is really good at taking the bad stuff out and leaving the good stuff in. This stage removes chlorine and other water-borne tastes and odors.



2. In-Tank UV: next, an in-tank UV (ultra-violet) lamp purifies the water. UV light wipes out harmful bacteria such as E. Coli, Salmonella and Hepatitis to guarantee a safe, clean drink.



3. BioCote®: we've got the inside covered and the outside too. As another layer of defense, BioCote keeps the dispensing area free of bacteria.









Performance Worthy of an Encore

- Hot, cold and ambient options
- Easy connection to your existing mains water supply
- Smart design with simple buttons and icons for ease of use
- Freestanding and counter top options to suit every workplace
- Sleek modern look ideal for the office environment



The Boring Bits

Water Options	Technical Features		
<ul style="list-style-type: none"> •   •   	Type available	Freestanding Counter top	
	Freestanding dimensions	W 345mm x H 1030mm x D 367mm W 13.6in x H 40.6in x D 14.5in	
	Counter top dimensions	W 345mm x H 480mm x D 367mm W 13.6in x H 18.9 in x D 14.5in	
	Dispense area height	215mm, 8.5in	
	Weight	Freestanding: 27-29KG Counter Top: 22-23KG	
Symbols	Standard filtration supplied (where applicable)	1 x Carbon Block (CBC) or 1 x Granular Activated Carbon (GAC)	
<ul style="list-style-type: none">  Ambient water  Cold water  Sparkling water  Hot water  Extra Hot water 	Additional features	Thermal Overload	
	Capacity	Freestanding Cold tank: 4 liter Hot tank: 1.5 liter	Counter top Cold tank: 2 liter Hot tank 1.5 liter
	Compressor	230v / 50Hz or 120v / 60Hz compressor	
	Water temperatures	Cold: 5-8°C / 41-46.4°F Hot: 87°C/189°F	

Tested and Certified



Waterlogic International Limited reserves the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo are registered trademarks in countries where the Group operates. Waterlogic International Limited is licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Speak to a Water Expert

USA, Canada and Mexico
info@waterlogicusa.com
 + 1 402 884 7212

Waterlogic USA,
 11710 Stonegate Circle,
 Omaha, NE 68164

Rest of the world
exportsales@waterlogic.com
 + 353 1 293 1960

WLI Trading Ltd.
 Suite 4, 2nd Floor Beacon Court,
 Sandyford, Dublin 18, Ireland
www.waterlogic.com

Visit Waterlogic

