

# WL350 Firewall™

## Drinking water you can trust for your office

The Waterlogic WL350 brings breakthrough Firewall™ water purification to your office in a compact model design. With high performance filtration and Firewall™ ultra violet technology that purifies water to 99.9999% bacteria free, you can now provide the best in water quality to your employees.



### Your Total Water Solution

The WL350 has three core technologies:



#### High Performance Filtration

Multi- stage filtration removes common water contaminants and chlorine to dramatically improve water taste and odor.



#### Firewall™ Advanced UV Purification

Firewall™ ultraviolet light purifies the water to 99.9999% bacteria free. It acts as a final barrier to pathogens right at the point of dispensing.



#### BioCote® Anti-Microbial Protection

BioCote® is a natural anti-microbial protection built in during manufacturing to reduce microorganism growth on the equipment surfaces.



## Our Firewall™ technology is unique for 3 reasons:

### 1. Intense UV purity

The design allows for higher UV exposure which reduces bacteria, viruses and parasites that may be in the water, purifying up to 99.9999% of any pathogens 100% of the time.

### 2. Goodbye bacterial contamination

Point of dispense purification keeps the dispense nozzle free from external contamination as well as purifying the water as it fills your cup, making the freshest water possible.

### 3. Certified, twice

The Firewall™ technology has been tested and certified by the Water Quality Association to NSF/ANSI-55 Class A UV and NSF P231 protocol, which is unique – no other system has these together.



WL350 Countertop Model

## Tested and Certified



Waterlogic International Limited reserves the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo are registered trademarks in countries where the Group operates. Waterlogic International Limited is licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

## Speak to a Water Expert

See business card for local distributor or visit [www.waterlogic.com](http://www.waterlogic.com)

Water Options	Technical Features	
	Counter top dimensions	345mm (W) x 480mm (H) x 367mm (D) 13.58" (W) x 18.8" (H) x 14.4" (D)
	Freestanding dimensions	345mm (W) x 1030mm (H) x 367mm (D) 13.58" (W) x 40.55" (H) x 14.4" (D)
	Dispense area height	210mm (8.25")
	Weight	Counter top: 26KG Freestanding: 30KG
Symbols	Standard filtration supplied	1 x Carbon Block (CBC)
 Cold water   Hot water	Additional features	Firewall™ UV sensor Thermal overload cut out
	Capacity	Hot tank: 1.5 liters (0.4 US gal.) Cold tank freestanding: 4 liters (1.06 US gal.) Cold tank counter top: 2 liters (0.53 US gal.)
	Compressor	230V (or 110v) /50Hz (60Hz) LG compressor
	Water temperatures	Cold 5°C/41°F Hot 87°C/189°F